



NOTES:

1. CURB RAMPS AND DETECTABLE WARNING MATERIALS MUST BE COMPLIANT WITH 2010 ADA STANDARDS FOR ACCESSIBLY DESIGN AND THE 2012 TEXAS ACCESSIBILITY STANDARDS (TAS).
2. DETECTABLE WARNING PANELS TO BE CAST-IN-PLACE CAST IRON DETECTABLE WARNING PLATES MANUFACTURED BY EAST JORDAN IRON WORKS OR NEENAH FOUNDRY.
3. DETECTABLE WARNING PANELS TO BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.
4. DETECTABLE WARNING PANEL SHALL BE LOCATED SUCH THAT THE EDGE NEAREST THE CURB LINE IS AT THE BACK OF CURB. ALIGN THE ROWS OF DOMES PERPENDICULAR TO THE GRADE BREAK BETWEEN THE RAMP RUN AND THE ROADWAY.
5. DETECTABLE WARNING PANEL TO BE COTNRASTING COLOR TO THE ADJACENT SURFACES, INCLUDING SIDE FLARES.
6. REBAR AND EXPANSION JOINTS TO BE INSTALLED PER CITY OF HUTTO DETAILS ST04 - SIDEWALK, ST02 - RESIDENTIAL DRIVEWAY, AND ST03 - COMMERCIAL DRIVEWAY
7. CONCRETE TO BE INSTALLED PER CITY OF HUTTO SPECIFICATIONS.



**CITY OF HUTTO
CONSTRUCTION STANDARDS AND DETAILS**

**STANDARD
CURB RAMP
ENGINEERING & PUBLIC WORKS**

DRAWING NO.	ST05
UPDATED:	02/01/2019
DRAWN BY:	BB
SCALE:	N.T.S.
FILE NAME:	ST05.DWG