

NOTES:

- FIRE HYDRANT SHALL BE INSTALLED ON THE SAME SIDE OF THE ROAD AS THE WATER MAIN.
- 2. FIRE HYDRANT SHALL BE INSTALLED PLUMB AND TRUE.
- ALL FIRE HYDRANT EXTERIORS SHALL BE FACTORY PRIMED AND PAINTED SILVER USING A CITY ENGINEER APPROVED 3. HIGH GRADE PAINT, INCLUDING BONNET.
- HEEL AND THRUST BLOCKS TO REST IN UNDISTURBED SOIL.
- THE ONLY FIRE HYDRANTS ACCEPTABLE ARE:
 - KENNEDY K81D
 - AMERICAN DARLING B84B
 - CLOW MEDALLION
- DOUBLE BLUE REFLECTOR "HYE-LITES" BRAND, MANUFACTURED BY PAVEMENT MARKERS, INC. TO BE INSTALLED AT CENTERLINE OF STREET PERPENDICULAR TO HYDRANT.
- ALL BOLTS SHALL BE STAINLESS STEEL
- ONLY ORIGINAL EQUIPMENT MANUFACTURE PARTS SHALL BE USED.



CITY OF HUTTO

CONSTRUCTION STANDARDS AND DETAILS

L FIRE HYDRANT INTALLATION

ENGINEERING & PUBLIC WORKS

DRAWING NO	O. W17
UPDATED:	04/01/2019
DRAWN BY:	BB
SCALE:	N.T.S.
FILE NAME:	W17.DWG